

VYBO Electric a.s.



Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	1ALZ-112M-4 6,3KW 400/690V 50HZ
Brand	VYBO Electric

Identification

Type:	1ALZ-112M-4	Frame:	112	mm
Power:	6,3 kW	Poles:	4	P
Speed:	1440 rpm	Rated Voltage:	400 / 690	V
Frequency:	50 Hz	Connection:	Δ/Y	
Rated Current:	400 V	12,9 A	Insulation Class:	
	690 V		7,5	
Efficiency:	IE1	84,7	Service Factor:	
	100%	86,7	1,0	
	75%	86,8	Duty:	
	50%	85,6	S1, S2, S3, S4-S9	
Power factor:	0,83	Ambient Temperature:	-35 ~ 50°C (On request possible 62°C)	
Noise level:	65 dB(A)	Altitude:	1000m	
Weight:	36,5 kg	Protection Degree:	IP55	
		Cooling:	IC411	
		Mounting:	IM B (On request)	
		Vibration:	2.8 mm/s	
		Direction of Rotation:	Both	
		Starting Method:	DOL or VFD	
		Coupling:	DIRECT	
		Load Type:	Parabolic or linear curve	
		Terminal box:	2-M35X1.5	



Bearing Information

	DE	NDE
Bearing:	63062Z	63062Z
Regreasing int.(h):		
Grease amount(g):		
Grease:		

Notes / Accessories

Deviation Sheet

	VYBO Electric		Customer

Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

Edition

Performed	Checked	Date

Item	Changes	Performed	Checked	Date