

VYBO Electric a.s.



Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	3LC-160L-4 15KW 400/690V 50HZ
Brand	VYBO Electric

Identification

Type:	3LC-160L-4	Frame:	160	mm
Power:	15 kW	Poles:	4	P
Rated Current:	400 V 27,3 A	Rated Voltage:	400 / 690	V
Speed:	1470 rpm	Connection:	Δ/Y	
Frequency:	50 Hz	Insulation Class:	F	
Direct on line starting torque ratio (LRT/RLT):	2,2	Temperature Rise:		
Direct on line pull out torque ratio (BDT/RLT):	2,3	Service Factor:	1,0	
Direct on line starting current ratio (LRA/RLA):	7,8	Duty:	S1, S2, S3, S4-S9	
Efficiency:	92,1 %	Ambient Temperature:	-35~40°C	
Power factor:	0,86	Altitude:	1000m	
Noise level:	73 dB(A)	Protection Degree:	IP55	
		Cooling:	IC411	
		Mounting:	IM B (On request)	
		Vibration:	2.8 mm/s	
		Direction of Rotation:	Both	
		Starting Method:	DOL or VFD	
		Coupling:	DIRECT	
		Load Type:	Parabolic or linear curve	
		Terminal box:	2-M40X1.5	



Bearing Information

	DE	NDE
Bearing:	6309-2RZC3	6309-2RZC3
Regreasing int.(h):		
Grease amount(g):		
Grease:		

Notes / Accessories

Deviation Sheet

	VYBO Electric		Customer

Standards

Specification:	IEC60034-1 / GB755	
Test:	IEC60034-2 / GB/T1032	
Noise:	IEC60034-9 / GB10069.3	
Vibration:	IEC60034-14 / GB10068	

Edition

Performed	Checked	Date



Item	Changes	Performed	Checked	Date