

# VYBO Electric a.s.



## Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer

Client reference

Type

4LC-315L 2-8 110KW 400/690V 50HZ

Brand

VYBO Electric

### Identification

Type:	4LC-315L 2-8		Frame:	315		mm
Power:	110	kW	Poles:	8		P
Rated Current:	380 V	213	Rated Voltage:	400	/	690 V
	400 V	202		Connection: Δ/Y		
	415 V	195		Insulation Class: F		
Speed:	740	rpm	Temperature Rise:			
Frequency:	50	Hz	Service Factor:	1,0		
Direct on line starting torque ratio (LRT/RLT):	1,6		Duty:	S1, S2, S3, S4-S9		
Direct on line pull out torque ratio (BDT/RLT):	2		Ambient Temperature:	-35~50°C		
Direct on line starting current ratio (LRA/RLA):	7,7		Altitude:	1000m		
Efficiency:	94,7	%	Protection Degree:	IP55		
Power factor:	0,81		Cooling:	IC411		
Noise level:	82	dB(A)	Mounting:	IM B (On request)		
Weight:	1311	kg	Vibration:	2.8 mm/s		
Rotor inertia:	8,3333	kg/m <sup>2</sup>	Direction of Rotation:	Both		
			Starting Method:	DOL or VFD		
			Coupling:	DIRECT		
			Load Type:	Parabolic or linear curve		
			Terminal box:	2-M63X1.5		



### Bearing Information

	DE	NDE
Bearing:	NU319C3	6319C3
Regreasing int.(h):		
Grease amount(g):		
Grease:		

### Notes / Accessories

### Deviation Sheet

Notes / Accessories		Deviation Sheet	
		VYBO Electric	Customer

### Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

### Edition

Performed	Checked	Date



Item	Changes	Performed	Checked	Date